



SITRAK | AUSTRALIA



SITRAK 8x4 T5G

Cab-Chassis or 7.6m³ AGI Turn-Key

- ◆ ALLISON 3200P Automatic
- ◆ HENDRICKSON Air Ride
- ◆ WABCO EBS Braking
- ◆ HARDOX Genuine 450
- ◆ REXROTH Pump & Motor
- ◆ PMP IND. Gearbox
- ◆ 2-Pak Truck & Mixer Paint
- ◆ MAN Extra Cabin & MAN 330hp

CABIN: MAN Extra Cab with Fold Down Day Bed and a Electric/Hydraulic Cab Lift

ENGINE: MAN MC07 @ 330hp (240kW @ 2300 rpm) / TORQUE: 1,250 Nm @ 1,200 – 1,800 rpm

TRANSMISSION: Allison 3200P Automatic with Chelsea Hotshift PTO

GVM: 31,000kg

FRONT AXLE & SUSPENSION: HF7 @ 7,000kg x 2 with Load Share Spring + FUPS

REAR AXLES & SUSPENSION: MCY13 @ 18,000kg (2) on 4-Bag Hendrickson Air
• C/W DCDL – Cross Locks

BRAKING: Dual Air Circuit - Disc Brakes + Exhaust Brake, WABCO EBS, ESC, EBL & ASR



Andrew Dosa - SITRAK Australia A BCI Company
☎ 61 434 358 074 ✉ andrew@sitrak.au
Dealer: MD29455

sitrak.au



SITRAK 8x4 T5G STANDARD TRUCK FEATURES

- ◆ 6 x Cabin Mirrors (4 x Adjustable)
- ◆ Windscreen Sun Visor & Roof Hatch
- ◆ 200L Alloy Fuel Tank & 45L DEF Tank
- ◆ ISRI Leather Air Driver Seat
- ◆ 4 Camera CCTV System
- ◆ Bluetooth & Dash Touch Screen
- ◆ Factory Climate Control Air Conditioning
- ◆ Wabco Air Dryer and Brake Valving
- ◆ Air Operated Steering Wheel Adjustment
- ◆ LH Cornering External Alarm
- ◆ Transmission Forced Neutral
- ◆ Door Park Brake Alarm
- ◆ Seat Belt Alarm
- ◆ Exhaust Brake System
- ◆ Day Time Running Lights
- ◆ Amber Beacon
- ◆ Cabin Fridge

TURN-KEY AVAILABLE - STANDARD 7.6M3 BASIC MIXER BOWL FEATURES

Skin	3mm Hardox 450
Fins (Mix, Discharge)	4mm - High strength, Wear resistant steel
Dished End	8mm High tensile, Wear and Corrosion resistant steel
Trunnion Rollers	Drop in Type 10,000kg rated (Greaseable with remote filling tubes)
Undercoat	2 Pak epoxy primer
Painting (Bowl and Frame)	2 Pak top coat polyurethane in PPG
Loading Hopper	3.0mm HARDOX 450
Discharge Hopper	3.0mm HARDOX 450 with Easy Clean Access
Swivel Chute Jack	Hydraulic with motor and pump
Gearbox	PMP Industries (Italy) PMB 6.5
Pump	Rexroth A10VGT071EPHW200
Motor	Rexroth A2FMT080
Hoses	Made to GB/T 10544 specifications
Hydraulic Tank	Combination Hydraulic Tank & Cooler with Fan
Water Tank	Pressurized 200 Lt aluminium with Slump gun, meter & slump hose
Additives Tank	Pressurized 100 Lt aluminium (Approx 100Lt)
Wheel Covers	Plastic drive and 2nd steer guards